

Lieferprogramm

Range of products



(EN)

impra[®]lan

The expert system for the industrial surface coating of wood

impra[®]lan is a water-based system designed for the industrial surface coating of wood.

Our products are as well-suited to wood as they are to highly complex industrial production processes. Irrespective of whether the wood to be treated is used in window frame construction, on balconies, fences or facades, the demands on our products are high. We guarantee prompt delivery and competent on-site service to help ensure the best possible result.

profilan[®]

Surface coatings for professionals

profilan[®] is the water- and solvent-based professional programme for the protection and improvement of wood used in- and outdoors.

Our matched primers, wood stains and opaque paint systems are guaranteed to meet even the most demanding design requirements. The challenge for our products has been set: the best possible workability, impressive results and optimum protection!

These are the goals we set in our research and development department to keep coming up with new ideas and products for you, linked with wood preservation, surface systems and maintenance.

impra[®]tec

Active wood protection









































The impra[®]tec product range combines efficacy and modern active ingredients to combat wood pests and better protect human health and the environment.



Our products fully comply with all current legal requirements.






















Detailed information on our products can be found in the relevant technical leaflet.

impra® lan













| Translucent coatings | | |
|--|---|----|
| Impregnation | | |
| impra®lan-Grund I100* |    | 8 |
| Translucent primers | | |
| impra®lan-Grund G100 |    | 9 |
| impra®lan-Grund G300* |    | 9 |
| impra®lan-Grund G400* |    | 10 |
| Translucent intermediate coatings | | |
| impra®lan-Füller F200 |   | 11 |
| impra®lan-Füller F710 |   | 11 |
| impra®lan-Vorlack V600 |    | 12 |
| impra®lan-Vorlack V710 |   | 12 |
| Translucent top coats | | |
| impra®lan-Lasur S100 / S150 |  | 13 |
| impra®lan-Lasur S200 |  | 13 |
| impra®lan-Lasur S500 / S550 |  | 14 |
| impra®lan-Natureffektlasur S510 |  | 14 |
| impra®lan-Lasur S600 |  | 15 |
| Opaque coatings | | |
| Opaque primers | | |
| impra®lan-Grund G200* |    | 16 |
| impra®lan-Grund G250* |    | 16 |
| impra®lan-Grund G500* |   | 17 |
| Opaque intermediate coatings | | |
| impra®lan-Füller F350 |   | 18 |
| impra®lan-Vorlack V100 |  | 18 |
| Opaque top coats | | |
| impra®lan-Decklack D100 / D150 |  | 19 |
| impra®lan-Decklack D200 |  | 19 |
| impra®lan-Decklack D600 |  | 20 |

*Use biocides safely. Always read labelling and product information before use.
Information on product application is only for reference purposes and may vary according to coating type.


Translucent products for timber construction








| | | |
|----------------------|---|----|
| impra®lan-Lasur T100 |    | 21 |
| impra®lan-Lasur T110 |     | 21 |
| impra®lan-Lasur T150 |  | 22 |
| impra®lan-Lasur T300 |   | 22 |
| impra®lan-Lasur T500 |   | 23 |
| impra®lan-Lasur T600 |     | 23 |
| impra®lan-Lasur S300 |    | 24 |
| impra®lan-Lasur S400 |   | 24 |

Opaque products for timber construction

| | | |
|----------------------------|---|----|
| impra®lan-Isoliergrund OSB |   | 25 |
| impra®lan-Vorlack V120 |   | 25 |
| impra®lan-Vorlack V215 |   | 26 |
| impra®lan-Decklack D300 |    | 26 |
| impra®lan-Decklack D400 |    | 27 |

Additional products

| | | |
|--------------------------------|---|----|
| impra®lan-Flex | | 28 |
| impra®lan-Fugensiegel | | 28 |
| impra®lan-Hirnholzversiegelung |  | 28 |
| impra®lan-Feinspachtel | | 29 |
| impra®lan-Pflegeset | | 29 |
| impra®lan-Reiniger | | 29 |
| impra®lan-Entschäumer | | 30 |
| impra®lan-Entschäumer select | | 30 |
| impra®lan-Additiv K* | | 30 |
| impra®lan-Additiv M | | 30 |
| impra®lan-Streichzusatz | | 31 |
| impra®lan-Härter WPU | | 31 |

Key:  = Spray,  = Dip,  = Flow coating,  = Vacuum coater,  = Brush application,  = Roller application,  = Board painting machine









*Use biocides safely. Always read labelling and product information before use.

Information on product application is only for reference purposes and may vary according to coating type.










Please read our General Terms and Conditions.

profilan®

Water-based surface coatings

| | | |
|--|---|----|
| profilan®-prevent* Imprägniergrund |   | 33 |
| profilan®-secur Isolierlack |    | 33 |
| profilan®-fina-Hybrid Dünnschichtlasur |  | 34 |
| profilan®-top Dickschichtlasur |   | 35 |
| profilan®-selva Holzöl |  | 35 |
| profilan®-opac Allwetterlack |    | 36 |
| profilan®-Holzentgrauer |  | 37 |

Solvent-based surface coatings

| | | |
|------------------------------------|---|----|
| profilan®-Holzschutzgrund B* |   | 39 |
| profilan®-Renovationsgrund |  | 39 |
| profilan®-lasol Imprägnierlasur |  | 40 |
| profilan®-lasol B* Imprägnierlasur |  | 40 |
| profilan®-color Langzeitlasur |  | 41 |
| profilan®-teoma Holzöl |  | 41 |
| profilan®-elan Dickschichtlasur |   | 42 |

Wood preservative

| | | |
|-----------------------|---|----|
| impra®tec-sanol I B * |  | 43 |
|-----------------------|---|----|

Key:  = Spray,  = Dip,  = Flow coating,  = Vacuum coater,  = Brush application,  = Roller application,  = Board painting machine

*Use biocides safely. Always read labelling and product information before use.
Information on product application is only for reference purposes and may vary according to coating type.

impra®lan - Industrielle Oberflächenbeschichtung | Industrial surface coatings



impfa® lan-Grund I100



Water-based impregnation for wood used outdoors

Biocidal primer for the protection against blue stain and rot according to DIN 68800 Part 3.

Fields of application: For the protection against blue stain and rot of all types of wood used outdoors above ground.

Properties:

- Strengthens wood and stabilises dimensions
- High penetration capacity at practice-oriented application rate
- Highly effective
- Quick drying
- Elements can be glued separately
- Levelling
- Moisture-regulating

Consumption: 80 – 100 ml/m² per coat

Colours: 0000 Colourless

| Pack size | Units per pallet (Product-No. W7093) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |

impfa® lan-Grund G100



Water-based primer for wood used in- and outdoors

Pigmented primer.

Fields of application: Primer without biocides for dimensionally stable and dimensionally unstable wooden elements. Especially suitable for priming windows and exterior cladding.

Properties:

- Low grain raising
- Quick drying
- Easy sanding
- Excellent flow properties
- Very good adhesion to the wood base
- Uniform pigmentation

Consumption: 60 – 80 ml/m² per coat

| | | | |
|-----------------|-------------------|-------------------|--------------------|
| Colours: | 0000 Colourless | 0200 Limba | 0749 Dark mahogany |
| | 0101 Light oak | 0300 Chestnut | 0750 Mahogany |
| | 0103 Antique oak | 0650 Wenge | 0805 Teak |
| | 0150 Pine | 0700 Walnut | 0850 Rosewood |
| | 0199 Antique pine | 0720 Light walnut | |

Other colours available on request.

Base for mixing:

| Pack size | Units per pallet (Product-No. W7051) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |
| 4.75 l can | 96 units |
| 19 l drum | 22 units |

impfa® lan-Grund G300



Water-based primer for wood used outdoors

Pigmented primer for protection against blue stain and rot according to DIN 68800 Part 3.

Fields of application: For the protection against blue stain and rot of statically unstressed wooden elements above ground.

Properties:

- Highly effective
- Very good adhesion to the wood base
- Quick drying
- Excellent penetration. The active ingredients fix particularly well on the surface.

Consumption: 80 – 100 ml/m² per coat

| | | | |
|-----------------|-------------------|-------------------|--------------------|
| Colours: | 0000 Colourless | 0200 Limba | 0749 Dark mahogany |
| | 0101 Light oak | 0300 Chestnut | 0750 Mahogany |
| | 0103 Antique oak | 0650 Wenge | 0805 Teak |
| | 0150 Pine | 0700 Walnut | 0850 Rosewood |
| | 0199 Antique pine | 0720 Light walnut | |

Other colours available on request.

Base for mixing:

| Pack size | Units per pallet (Product-No. W7096) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |
| 4.75 l can | 96 units |
| 19 l drum | 22 units |

impfa[®] lan-Grund G400



Water-based primer for wood used outdoors

Pigmented or colourless, biocidal primer for protection against blue stain and rot.

Fields of application: For the protection against blue stain and rot of all types of wood above ground. Especially suitable for priming window frames and exterior cladding.

Properties:

- Excellent levelling and flowing properties
- Easy sanding
- Low grain raising
- Very good adhesion to the wood base
- Optimal pore filling
- Quick drying

Consumption: 80 – 100 ml/m² per coat

| | | |
|-----------------|-------------------|--------------------|
| Colours: | 0000 Colourless | 0650 Wenge |
| | 0101 Light oak | 0700 Walnut |
| | 0103 Antique oak | 0720 Light walnut |
| | 0150 Pine | 0749 Dark mahogany |
| | 0199 Antique pine | 0750 Mahogany |
| | 0200 Limba | 0805 Teak |
| | 0300 Chestnut | 0850 Rosewood |

Other colours available on request.

Base for mixing:

| Pack size | Units per pallet (Product-No. W7090) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |
| 19 l drum | 22 units |

impra® lan-Füller F200



Water-based intermediate coating for wood used in- and outdoors

Colourless, cost-effective intermediate coating. Very good saturation of end grain.

Fields of application: For doors, window frames and other dimensionally stable and dimensionally unstable wood components.

Properties:

- Very good pore filling and end grain saturation
- Mild odour
- Good sanding properties
- Block resistant

Consumption: 60 – 80 ml/m² per coat

Colours: 0000 Colourless

Pack size

Units per pallet (Product-No. W7128)

20 l drum

22 units

120 l drum

4 units

1.000 l IBC

on request

impra® lan-Füller F710



Water-based transparent intermediate coating for wood used in- and outdoors

Isolating intermediate coating for flow-coating.

Fields of application: Intermediate coating for doors and windows. Also suitable for use on other dimensionally stable and dimensionally unstable wooden elements in- and outdoors.

Properties:

- Delivered ready to use by flow-coating
- Transparent
- Isolating
- Very good pore filling
- Particularly suitable for treating larch wood

Consumption: 60 – 80 ml/m² per coat

Colours: 0000 Colourless

Pack size

Units per pallet (Product-No. W7213)

20 l drum

22 units

120 l drum

4 units

1.000 l IBC

on request

impfa® lan-Vorlack V600



Water-based isolating colourless primer for MDF used in- and outdoors



Fields of application: Sealing primer for MDF.

Properties:

- Reduces water absorption (MDF)
- Very good blocking properties
- Mild odour
- Quick-drying

Consumption: 150 – 175 ml/m² per coat

Colours: 0000 Colourless

| Pack size | Units per pallet (Product-No. W7050) |
|------------|---|
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 120 l drum | 4 units |

impfa® lan-Vorlack V710



Water-based intermediate coating for wood used in- and outdoors

Colourless, isolating intermediate coating to be used by spraying and brushing.



Fields of application: Intermediate coating for doors and windows. Also suitable for use on other dimensionally stable and dimensionally unstable wooden components both inside and out.

Properties:

- Supplied ready to use by spraying
- Transparent
- Isolating
- Good pore filling
- Suitable for treating larch wood

Consumption: 150 – 175 ml/m² per coat by spray
60 – 80 ml/m² per coat by brush; 2x application

Colours: 0000 Colourless

| Pack size | Units per pallet (Product-No. W7214) |
|------------|---|
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 120 l drum | 4 units |

impfa®lan-Lasur S100 seidengläzend | silk gloss

impfa®lan-Lasur S150 seidenmatt | silk matt



Water-based, film-forming wood stain for both interior and exterior wood

Transparent wood stain with high filling properties and excellent UV protection.

Fields of application: Intermediate and top coating of window frames and doors and other dimensionally stable wooden components, according to the guidelines of Institut für Fenstertechnik e.V. Rosenheim, Germany.

Properties:

- Highly elastic and block resistant
- High UV stability
- Suitability certified according to DIN EN 927-2
- Saliva- and sweat resistant according to DIN EN 71-3

Consumption: 300 ml/m²; in 1 – 2 coats

| | | |
|-----------------|------------------|---------------------|
| Colours: | 0000 Colourless* | 0650 Wenge |
| | 0101 Light oak | 0700 Walnut |
| | 0103 Antique oak | 0710 Light walnut |
| | 0150 Pine | 0749 Dark mahogany |
| | 0152 Ash | 0753 Light mahogany |
| | 0200 Limba | 0805 Teak |
| | 0300 Chestnut | 0850 Rosewood |

Other colours available on request.

Base for mixing:

* 0000 Colourless should never be applied as finish outdoors.



| Pack size | Units per pallet (Product-No. W7115) |
|-------------|---|
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |
| 4.75 l can | 96 units |
| 19 l drum | 22 units |

impfa®lan-Lasur S200 glänzend | gloss



Water-based, film-forming wood stain for both interior and exterior wood

Transparent, glossy wood stain with high filling properties.

Fields of application: Intermediate and top coating of window frames, doors and other dimensionally stable wooden components, according to the guidelines of Institut für Fenstertechnik e.V. Rosenheim, Germany.

Properties:

- Highly elastic and block resistant
- High UV stability
- Suitability certified according to DIN EN 927-2

Consumption: 300 ml/m², in 1 – 2 coats

Colours: 0000 Colourless*

Other colours available on request.

Base for mixing:

* 0000 Colourless should never be applied as finish outdoors.



| Pack size | Units per pallet (Product-No. W7104) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |
| 19 l drum | 22 units |

impfa® lan-Lasur S500 seidenglänzend | silk gloss



impfa® lan-Lasur S550 seidenmatt | silk matt

Water-based, film-forming wood stain for wood used indoors.

Transparent wood stain with high filling properties.

Fields of application: Top coat for high quality wooden elements, such as timber / aluminium window frames, doors, panels, etc.

Properties:

- High filling properties
- Block resistant
- Resistant to scratches
- Saliva- and sweat-resistant according to DIN EN 71-3
- PU-reinforced

Consumption: 300 ml/m², in 1 – 2 coats

Colours: 0000 Colourless

Mixed tints white collection:

| | | |
|---------------------|------------------|--|
| 0052 Soft white | 0082 Grey white | |
| 0062 Smoke white | 0092 Cream white | |
| 0072 Platinum white | | |

Other colours available on request.

Base for mixing:



| Pack size | Units per pallet (Product-No. W7131) (Product-No. W7179) |
|------------|--|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 4.75 l can | 96 units |
| 19 l drum | 22 units |

impfa® lan-Natureffektlasur S510



Water-dilutable, dead matt wood stain for wood used in- and outdoors

Wood stain with high scratch resistance and pleasant to touch.

Fields of application: Top coat for high quality wooden elements, such as timber / aluminium window frames, doors and panels.

Properties:

- | | |
|------------------------------|--|
| – „Soft feel“ effect | – Block resistant |
| – „Untreated timber“ look | – Highly translucent |
| – Protects against yellowing | – Saliva- and sweat-resistant according to DIN EN 71-3 |
| – Scratch resistant | |

Consumption: 180 – 220 ml/m² per coat

Gloss level: Dead matt

Colours: 0000 Colourless
0216 Transparent oak
0401 Transparent larch

Other colours available on request.

Base for mixing:



| Pack size | Units per pallet (Product-No. W7189) |
|------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 19 l drum | 22 units |

impra® lan-Lasur S600



Water-based, film-forming wood stain for use on front doors

Water-based, film-forming wood staining for wood used in- and outdoors and exposed to mechanical stain. Particularly suitable for front doors.

Fields of application: Intermediate and top coat for wooden elements used in- and outdoors. Particularly suitable for dimensionally stable wooden components such as front doors.

Properties:

- High level of opacity
- Elastic and block resistant
- Extended resistance to weathering
- High UV stability
- Very good covering of edges
- Mild odour
- Free of microfoam
- Single-component
- Resistant to mechanical strain
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 150 – 175 ml/m² per coat

Gloss level: Silk gloss

| | | | |
|-----------------|------------------|-------------------|---------------------|
| Colours: | 0000 Colourless* | 0200 Limba | 0749 Dark mahogany |
| | 0101 Light oak | 0300 Chestnut | 0753 Light magohany |
| | 0103 Antique oak | 0650 Wenge | 0805 Teak |
| | 0150 Pine | 0700 Walnut | 0850 Rosewood |
| | 0152 Ash | 0710 Light walnut | |

Other colours available on request.

Base for mixing:

* 0000 Colourless should never be applied as finish outdoors.

| Pack size | Units per pallet (Product-No. W7208) |
|------------|---|
| 2.5 l tin | 144 units |
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 2.25 l tin | 144 units |
| 4.75 l can | 96 units |
| 19 l drum | 22 units |

impfa[®]lan-Grund G200



Water-based white primer for wood used outdoors

Opaque, white primer for flow-coating and dipping.

Fields of application: White primer with good wet adhesion and good flowing properties. Particularly suitable for priming windows and exterior cladding.

Properties:

- Excellent flow properties
- Very good adhesion to the wood base
- Optimal pore filling
- Low grain raising

Consumption: 80 – 100 ml/m² per coat

Colours: 9110 White

| Pack size | Units per pallet (Product-No. W7025) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |

impfa[®]lan-Grund G250



Water-based translucent white primer for wood used outdoors

Translucent white, biocidal primer for the protection against blue stain and rot according to DIN 68800 Part 3.

Fields of application: For the protection against blue stain and rot of all types of wood used outdoors above ground. Especially suitable for priming windows and exterior cladding.

Properties:

- Excellent flow properties
- Low grain raising
- Very good adhesion to the wood base
- Excellent penetration
- Delivered ready to use

Consumption: 80 – 100 ml/m² per coat

Colours: 0002 White transparent

| Pack size | Units per pallet (Product-No. W7038) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |

impra® lan-Grund G500



Water-based white primer for wood used outdoors

White, biocidal primer for the protection against blue stain and rot.

Fields of application: For the protection against blue stain and rot of all types of wood above ground. Especially suitable for priming window frames and exterior cladding.

Properties:

- Mild odour, odourless after drying
- Easy sanding
- Low grain raising
- Very good adhesion to the wood base
- Optimal pore filling
- Quick drying

Consumption: 80 – 100 ml/m² per coat

Colours: 9110 White

| Pack size | Units per pallet (Product-No. W7066) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |

impfa[®]lan-Füller F350



Water-based white primer and intermediate coating for wood used in- and outdoors

White primer and intermediate coating with very good isolating properties against water soluble wood infiltrates.

Fields of application: For doors, window frames and other dimensionally stable and dimensionally unstable wooden components. Especially suitable for use on oak and other types of hardwood.

Properties:

- Very good blocking properties
- Very good pore filling and end grain saturation
- Good sanding properties
- High dry film thickness
- No discolouration of the finish
- Excellent adhesion

Consumption: 60 – 80 ml/m² per coat

Colours: 9110 White

| Pack size | Units per pallet (Product-No. W7158) |
|-------------|---|
| 20 l drum | 22 units |
| 50 l drum | 6 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |

impfa[®]lan-Vorlack V100



Water-based isolating white primer for both interior and exterior wood

White intermediate coating with very good isolating properties against soluble timber ingredients in a one-coat application.

Fields of application: For doors, window frames and other dimensionally stable and dimensionally unstable wooden components. Especially suitable for use on hard- and softwoods.

Properties:

- Very good blocking properties
- Optimised covering of edges
- High filling properties

Consumption: 175 – 200 ml/m² per coat

Colours: 9110 White

| Pack size | Units per pallet (Product-No. W7004) |
|------------|---|
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 50 l drum | 6 units |
| 120 l drum | 4 units |

impfa®lan-Decklack D100 seidenglänzend | silk gloss

impfa®lan-Decklack D150 seidenmatt | silk matt



Water-based opaque paint for wood used in- and outdoors

Top coat with extremely high covering properties and extended resistance to weathering.

Fields of application: Intermediate and top coat for window frames, doors and other dimensionally stable wooden elements, according to the guidelines of Institut für Fenstertechnik e.V. Rosenheim, Germany.

Properties:

- Highly elastic and block resistant
- Very good covering of edges
- Suitability certified according to DIN EN 927-2
- Free of micro foam
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 300 ml/m², in 1 – 2 coats

Colours: RAL 9010 Pure white RAL 9016 Traffic white 9110 White

Other colours available on request.

Base for mixing: Base A (White)
 Base C (Transparent)



| Pack size | Units per pallet (Product-No. W7116) (Product-No. W7100) |
|-------------|--|
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 50 l drum | 6 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |
| 2.5 l tin | 144 units |
| 5 l can | 96 units |
| 10 l drum | 30 units |
| 20 l drum | 22 units |
| 50 l drum | 6 units |
| 120 l drum | 4 units |
| 2.25 l tin | 144 units |
| 4.5 l can | 96 units |
| 9 l drum | 30 units |
| 18 l drum | 22 units |
| 45 l drum | 6 units |
| 108 l drum | 4 units |

impfa®lan-Decklack D200 glänzend | gloss



Water-based opaque paint for wood used in- and outdoors

Glossy opaque paint with extended resistance to weathering.

Fields of application: Intermediate and top coat for window frames, doors and other dimensionally stable wooden components, according to the guidelines of Institut für Fenstertechnik e.V. Rosenheim, Germany.

Properties:

- Highly elastic and block resistant
- Very good covering of edges
- Suitability certified according to DIN EN 927-2
- Free of micro foam
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 300 ml/m², in 1 – 2 coats

Colours: RAL 9010 Pure white 9110 White
 RAL 9016 Traffic white

Other colours available on request.

Base for mixing: Base A (White)
 Base C (Transparent)



| Pack size | Units per pallet (Product-No. W7105) |
|------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 9 l drum | 30 units |
| 18 l drum | 22 units |

impfa[®]lan-Decklack D600



Water-based opaque paint for wood used in- and outdoors

Water-based opaque paint for wood used in- and outdoors and exposed to mechanical strain. Particularly suitable for use on front doors.

Fields of application: For wooden elements used in- and outdoors. Particularly suitable for treating dimensionally stable wooden elements such as front doors.

Properties:

- High covering properties
- Elastic and block resistant
- Extended resistance to weathering
- Very good covering of edges
- Mild odour
- Free of micro foam
- Single-component
- Resistant to mechanical strain

Consumption: 150 – 175 ml/m² per coat

Colours: 9110 White

Other colours available on request.

Base for mixing: Base A (White)
Base C (Transparent)

| Pack size | Units per pallet (Product-No. W7209) |
|------------|---|
| 2.5 l tin | 144 units |
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 2.25 l tin | 144 units |
| 4.5 l can | 96 units |
| 18 l drum | 22 units |

impfa[®]lan-Lasur T150



Water-based wood stain to be used for flow-coating of wood used in - and outdoors

UV-resistant wood stain for flow-coating with film protection against mould and algae for a high quality look.

Fields of application: Intermediate coat and finish for wooden elements suitable to be treated by flow-coating and used outdoors above ground, e.g. fences, sight barriers, balcony railings, etc.

Properties:

- Optimised levelling
- Excellent flow properties
- Light- and weather-resistant stain
- Very good UV resistance
- Quick-drying
- Block resistant
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 80 – 100 ml/m² per coat

Colours: 9010 White gloss

Other colours available on request.

Base for mixing:

| Pack size | Units per pallet (Product-No. W7202) |
|------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 19 l drum | 22 units |

impfa[®]lan-Lasur T300



Water-based wood stain for structural wood

Transparent wood stain for the protection of structural wood against absorption of moisture and soiling during transport and construction.

Fields of application: For the protection of glue laminated beams and other structural wood against water splashes and soiling during transport and constructions.

Properties:

- Easy to apply
- No blocking of wet stacked timber
- Quick-drying
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 80 – 100 ml/m² per coat

Colours: 0000 Colourless

Other colours available on request.

| Pack size | Units per pallet (Product-No. W7120) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |

impfa[®]lan-Lasur S300



Water-based, film-forming wood stain for both interior and exterior wood

Transparent wood stain with high filling properties.

Fields of application: Intermediate and top coating for wall and ceiling claddings, pergolas, facades, balcony railings, etc.

Properties:

- Highly elastic and block resistant
- High UV stability
- Suitability certified according to DIN EN 927-2
- Excellent flow characteristics
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 60 – 125 ml/m², in 1 coat

Gloss level: Silk gloss

| | | |
|-----------------|------------------|---------------------|
| Colours: | 0000 Colourless* | 0650 Wenge |
| | 0101 Light oak | 0700 Walnut |
| | 0103 Antique oak | 0710 Light walnut |
| | 0150 Pine | 0749 Dark mahogany |
| | 0152 Ash | 0753 Light mahogany |
| | 0200 Limba | 0805 Teak |
| | 0300 Chestnut | 0850 Rosewood |

Other colours available on request.

Base for mixing:

* 0000 Colourless should never be applied as finish outdoors.

| Pack size | Units per pallet (Product-No. W7119) |
|------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 4.75 l can | 96 units |
| 19 l drum | 22 units |



impfa[®]lan-Lasur S400



Water-based wood stain for interior wood

Interior wood stain with high filling properties.

Fields of application: Top coat for wooden elements indoors, such as profiled boards, ceiling panels, etc.

Properties:

- Good filling properties
- Block resistant
- Quick drying
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 60 – 80 ml/m² per coat

Gloss level: Silk gloss

Colours: 0000 Colourless

Other colours available on request.

| Pack size | Units per pallet (Product-No. W7110) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |



impra®lan-Isoliergrund OSB



Water-based, highly opaque primer and top coat with isolating properties for OSB panels

Primer and top coat for OSB panels, structural wood and various wooden materials not directly exposed to weathering.

Fields of application: For OSB substrates (e.g. chipboard). Highly opaque primer and top coat for preventing discolouration and bleeding of soluble timber ingredients.

Properties:

- High level of opacity
- Highly effective against bleeding of soluble timber ingredients
- Good filling properties
- Quick-drying

Consumption: 100 – 120 ml/m² per coat

Colours: RAL 9010 Pure white

| Pack size | Units per pallet (Product-No. W7000) |
|-----------|---|
| 10 l drum | 30 units |
| 20 l drum | 22 units |

impra®lan-Vorlack V120



Water-based isolating white primer for both interior and exterior wood

White intermediate coating with very good isolating properties against soluble timber ingredients.

Fields of application: For profiled boards, facades and other dimensionally stable and dimensionally unstable wooden components.

Properties:

- Very good blocking properties
- Optimal edge coverage
- High filling properties

Consumption: 100 – 120 ml/m² per coat

Colours: 9110 White

| Pack size | Units per pallet (Product-No. W7008) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |

impfa[®]lan-Vorlack V215



Water-based primer and intermediate coating for wood used in- and outdoors

Cost-effective white primer and intermediate coating.

Fields of application: For profiled boards, facades as well as other dimensionally stable and dimensionally unstable wooden components.

Properties:

- Block resistant
- High filling properties
- Quick-drying
- Mild odour
- Reduced consumption rate
- High level of opacity

Consumption: 80 – 100 ml/m² per coat

Colours: 9110 White

| Pack size | Units per pallet (Product-No. W7015) |
|-------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 1.000 l IBC | on request |

impfa[®]lan-Decklack D300



Water-based opaque paint for wood used outdoors

Medium-build lacquer with high weather resistance and a film protection against mould and algae.

Fields of application: Intermediate and top coat for wooden elements used outdoors such as walls, soffits, pergolas, facades and balcony railings.

Properties:

- Suitability certified according to DIN EN 927-2
- Highly elastic and block resistant
- Very good covering of edges
- Effective against mould and algae
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 80 – 150 ml/m² per coat

Gloss level: Silk gloss

Colours: RAL 9010 Pure white

Other colours available on request.

Base for mixing: Base A (White)
Base C (Transparent)

| Pack size | Units per pallet (Product-No. W7117) |
|------------|---|
| 20 l drum | 22 units |
| 120 l drum | 4 units |
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 4.5 l can | 96 units |
| 18 l drum | 22 units |

impra[®] lan-Decklack D400



Water-based metallic top coat for use on both interior and exterior wood

Metallic effect coat for transparent- and opaque coatings. Enhances the natural grain of the timber and gives a natural greying effect with metallic pigments (only grey colour shades). With film protection against mould and algae.

Fields of application: Intermediate and top coat for wooden elements, such as fasades, glue laminated wood, carports, garden fences, soffits, etc. Particularly suitable for the re-coating of window frames.

Properties:

- Very good UV resistance
- Block resistant and water vapour permeable
- Optimised flow properties
- Quick-drying
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 80 – 120 ml/m², in 1 – 2 coats

| | | |
|-----------------|---------------------------|------------------|
| Colours: | 0951 Outback** | 2100 Savanna |
| | 0952 Nordic 1** | 3100 Arizona red |
| | 0953 Silverstyle moon 1** | 4100 Provence |
| | 0954 Silverstyle moon 2** | 5100 Ocean blue |
| | 0955 Mocha star | 6100 Tropical |
| | 1100 Golden beach | 8100 Cashmere |

Other colours available on request.

Base for mixing: Base metallic

** with greying effect

| Pack size | Units per pallet (Product-No. W7125) |
|-----------|---|
| 5 l can | 96 units |
| 20 l drum | 22 units |
| 4.5 l can | 96 units |
| 18 l drum | 22 units |

impra®lan-Flex



Plasto-elastic joint sealant

Water-based, acrylate sealant for sealing connection joints and V-joints on wooden window frames.

Fields of application: For the sealing of joints between wood, metal and plastic doors and other components and the structural shell. For all joints exposed to tensile stress in the facade area.

Properties:

- Low odour, elastic acrylate sealant
- Can be re-coated with most commercially available coating systems
- Good adhesion on almost all substrates
- Immediately rainproof
- Resistant to ageing and weathering

Colours: 0000 Colourless 9110 White

| Pack size | VPE (Product-No. W7203) |
|------------------|----------------------------|
| 310 ml cartridge | 10 pieces |

impra®lan-Fugensiegel



Water-based colourless sealer for open joints

Protective sealer for the end grain of open V-joints.

Fields of application: Protective sealer for the end grain of open V-joints on wooden doors, window frames and wooden components against water absorption in- and outdoors.

Properties:

- No discolouration (yellowing)
- Good saturation of the end-grain

Colours: 0000 Colourless

| Pack size | VPE (Product-No. W7118) |
|---------------|----------------------------|
| 250 ml bottle | 10 pieces |

impra®lan-Hirnholzversiegelung



Water-based sealant for use on end grain surfaces

Transparent sealant for preventing moisture penetration on end grain surfaces.

Fields of application: For the re-treatment and sealing of end grain surfaces and cut sites on both interior and exterior wooden components, e.g. decking, cut edge, etc.

Properties:

- Protects against water penetrating the end-grain
- Compatible with subsequent coats of water-based products

Consumption: Depends on the absorption capacity of the wood.

Colours: 0000 Colourless

| Pack size | VPE | Units per pallet (Product-No. W7123) |
|------------|-----|---|
| 0.25 l tin | 6 | 90 units |
| 0.75 l tin | - | 462 units |
| 2.5 l can | - | 144 units |

impra®lan-Feinspachtel

Water-based, quick drying dispersion putty

Fields of application: For filling and repairing when applying opaque systems on primed wood.

Properties:

- Very quick drying
- Good filling properties, environmentally compatible
- No cracking up to approx. 1000 microns wet film thickness
- Excellent sanding characteristics

Application: Spatula

Colours: White



| Pack size | VPE (Product-No. W7918) |
|------------|----------------------------|
| 400 g tube | 12 pieces |

impra®lan-Pflegeset | Care set

impra®lan-Special Cleaner and impra®lan-Wood Care Lotion

For the protection and maintenance of wooden doors and windows frames coated with impra®lan products.

Fields of application: For the regular care and maintenance of coated wooden doors and window frames.

Properties:

impra®lan-Special Cleaner

- Water-based
- High cleaning power
- Gentle to surfaces

impra®lan-Wood Care Lotion

- Renews the gloss
- Repairs small mechanical damage
- Additional protection against weathering

Application: Cloth

Colours: **impra®lan-Special Cleaner:** Transparent green

impra®lan-Wood Care Lotion: Colourless



| Pack size | VPE (Product-No. W7919) |
|--------------------------|----------------------------|
| Set 2 x 500 ml bottle | 10 pieces |

impra®lan-Reiniger

Cleaner for application equipment

Cleaning solution for vacuum coaters, spray equipment, flow-coating plants and recycling systems. Also suitable for the cleaning of brushes and other application tools. Dosage 1:5 (1 part concentrate, 5 parts water). Stronger solutions can be used where soiling is extensive.

Properties:

- Low in odour and effective
- High cleaning power

| Pack size | VPE | Units per pallet (Product-No. W7186) |
|----------------|-----|---|
| 2.5 l canister | 4 | 36 boxes |
| 20 l canister | – | 24 canisters |

impra®lan-Entschäumer

Defoaming agent for primers, wood stains and opaque paints

De-aerating agent for reducing foaming in vacuum coaters and flow-coating applications.

Dosage: 0.2 – 0.5 %

Properties:

- Highly effective
- High level of compatibility

| Pack size | VPE | Units per pallet (Product-No. W7192) |
|----------------|-----|---|
| 2.5 l canister | 4 | 36 boxes |

impra®lan-Entschäumer select

Defoaming agent for products applied by flow-coating or vacuum coaters

De-aerating agent for reducing foaming in vacuum coaters and flow-coating applications.

Dosage: 0.5 – 2 %

Properties:

- Reduces micro foam
- Solvent-free

| Pack size | VPE | Units per pallet (Product-No. W7210) |
|----------------|-----|---|
| 2.5 l canister | 4 | 36 boxes |

impra®lan-Additiv K

Biocidal additive with fungicidal and bactericidal efficacy

Biocidal additive for eliminating germs in flow-coating and dip applications.

Dosage: 0.3 – 1 %

Properties:

- Highly effective
- Low in odour

| Pack size | Units per pallet (Product-No. W7173) |
|--------------|---|
| 5 l canister | 84 canisters |

impra®lan-Additiv M

Matting additive for impra®lan products

impra®lan-Additiv M is used for the matting of impra®lan products. It gives surfaces an uniform matt and velvety finish.

Dosage: 2 – 3 %

Properties:

- High matting level
- Easy handling

| Pack size | Units per pallet (Product-No. W7170) |
|------------|---|
| 1 l bottle | – |

impra®lan-Streichzusatz

Additive to adjust to brushing consistency water-dilutable, industrial high-build coatings

Improves the brushability of high-build spray products to be used for touching up slight damages on recently coated window frames such as may occur during transport or fitting.

Dosage: 3 – 5 %

Properties:

- Water-dilutable
- Low in odour

Compatible with all impra®lan products.

| Pack size | Units per pallet (Product-No. W7132) |
|------------|---|
| 1 l bottle | – |

impra®lan-Härter WPU

Hardener component for water-based products

Hardener for impra®lan-Lasur S600 and impra®lan-Decklack D600, water-based coatings for front doors.

Properties:

- Low in odour and effective
- Improves the scratch resistance and hardness
- Accelerates the drying process

Consumption: 200 ml per 2.5 Liter

| Pack size | Units per pallet (Product-No. W7294) |
|-------------|---|
| 1 kg bottle | – |

profilan[®] - Wasserbasierende Oberflächenbeschichtung für das Handwerk
Water-based surface coatings for professionals



profilan[®]-prevent Imprägniergrund Impregnating primer



Water-based impregnating primer for wood used outdoors

Biocidal primer for the protection against blue stain, rot and insects according to DIN 68800 part 3. Efficacy certified according to DIN EN 113 and DIN EN 152-1.

Fields of application: For the protection against mould, blue stain and rot of wood used above ground and not statically loaded.

Properties:

- Deep, lasting protection
- Provides excellent adhesion of following coatings
- Odourless after drying

Consumption: 80 – 100 ml/m² per coat

Colours: 0000 Colourless

| Pack size | VPE | Units per pallet (Product-No. W7022) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 10 l drum | – | 30 units |
| 200 l drum | – | 2 units |

profilan[®]-secur Isolierlack Isolating primer and top coat



Water-based isolating primer for wood used in- and outdoors

White primer and intermediate coating with isolating properties against bleeding of tannins contained in wood.

Fields of application: For the priming of structural wood to be coated with water-based bright opaque paints.

Properties:

- Highly efficient against the bleeding of tannins contained in wood
- Quick drying
- High level of opacity
- Block resistant
- Excellent levelling properties

Consumption: 80 – 100 ml/m² per coat

Colours: 9110 White

| Pack size | VPE | Units per pallet (Product-No. W7002) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 10 l drum | – | 30 units |
| 20 l drum | – | 22 units |

profilan[®]-fina-Hybrid Dünnschichtlasur Low build wood stain



Water-based low build wood stain with high UV protection for wood used in- and outdoors

Transparent wood stain which enhances the natural grain of timber. Protection against mould and algae.

Fields of application: For all wooden elements, e.g. wall and ceiling panelling, doors, shelves, soffits, boarding, pergolas, balcony railings, etc.

Properties:

- Optimised flow properties
- Moisture regulating
- Low grain raising
- Breathable
- Dries evenly without brush marks
- Rainproof soon after application
- Highly weather resistant
- Excellent adhesion
- Wide range of colours available
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 60 – 80 ml/m² per coat

Gloss level: Satin matt

| | | |
|-----------------|------------------|-------------------|
| Colours: | 0000 Colourless* | 0300 Chestnut |
| | 0101 Light oak | 0700 Walnut |
| | 0103 Antique oak | 0710 Light walnut |
| | 0150 Pine | 0750 Mahogany |
| | 0200 Limba | 0850 Rosewood |

| | |
|-----------------------------|------------------|
| Greying wood stains: | 0706 Ice Stone |
| | 0707 Grey Nature |
| | 0708 Night Grey |
| | 0709 Fog Grey |

Other colours available on request.

Base for mixing:

* 0000 Colourless should never be applied as finish outdoors.

| Pack size | VPE | Units per pallet (Product-No. W7111) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 10 l drum | – | 30 units |
| 2.5 l tin | – | 36 boxes |
| 10 l drum | – | 30 units |
| 2.25 l tin | – | 36 boxes |
| 9 l drum | – | 30 units |

profilan®-top Dickschichtlasur

High build wood stain



Water-based high build wood stain for indoor and outdoor use

Transparent wood stain with high solids content. Preventive protection against mould and algae.

Fields of application: For all wooden elements, especially for timber components with dimensional stability, e.g. window frames, according to the guidelines for Institut für Fenstertechnik e.V. Rosenheim, Germany.

Properties:

- Good filling properties with very long-lasting weather protection
- Block resistant
- Very high level of transparency
- Silk gloss finish
- Suitability tested according to DIN EN 927-2
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 80 – 100 ml/m² per coat

Gloss level: Silk gloss

Colours:

| | | |
|------------------|------------------|-------------------|
| 0000 Colourless* | 0103 Antique oak | 0700 Walnut |
| 0005 Light grey | 0150 Pine | 0710 Light walnut |
| 0081 Opal white | 0200 Limba | 0750 Mahogany |
| 0101 Light oak | 0300 Chestnut | 0850 Rosewood |

Other colours available on request.

Base for mixing: Do not use profilan®-top Base as „Colourless“ or to lighten the standard colours.

* 0000 Colourless should never be applied as finish outdoors.

| Pack size | VPE | Units per pallet (Product-No. W7112) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 10 l drum | – | 30 units |

| | | |
|-------------|---|----------|
| 0.675 l can | – | 77 boxes |
| 2.25 l can | – | 36 boxes |
| 9 l drum | – | 30 units |

profilan®-selva Holzöl | Oil



Water-based oil for wood used outdoors

Deeply penetrating surface protection based on vegetable oils.

Fields of application: For the initial coating and maintenance of wood used outdoors. Also suitable for use on both exotic and hard woods.

Properties:

- Water repellent and weather resistant
- Long open time
- Low odour
- Easy to apply without brush marks
- Pleasant to touch
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 60 – 80 ml/m² per coat

Colours:

| | |
|------------------|----------------|
| 0009 Nature* | 0270 Bangkirai |
| 0210 Douglas fir | 0800 Teak |

Other colours available on request.

* 0009 Nature should never be applied as finish outdoors.

| Pack size | VPE | Units per pallet (Product-No. W7215) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 20 l drum | – | 22 units |

profilan[®]-opac Allwetterlack All-weather paint



Water-based, all-weather paint for wood used in- and outdoors

Highly weather-resistant paint with film protection against mould and algae.

Fields of application: For timber e.g. framework, balconies, wooden facades, window frames, doors, summerhouses, etc. After appropriate pre-treatment also suitable for treating brickwork, concrete, plaster, hard PVC, zinc and galvanised steel.

Properties:

- Highly opaque and diffusing
- Excellent adhesion on sound previous coats
- Effective against mould and algae
- Suitability certified according to DIN EN 927-2
- Block resistant
- Saliva- and sweat-resistant according to DIN EN 71-3

Consumption: 80 – 100 ml/m² per coat

Gloss level: Silk gloss

Colours:

| | |
|-------------------|------------------|
| 1102 Sahara | 7135 Agate |
| 1117 Yellow ochre | 7140 Opal white |
| 3101 Red | 8108 Bark brown |
| 3111 Crimson | 8117 Chocolate |
| 3140 Sweden red | 9105 Black |
| 6105 Fir green | 9010 Birch white |
| 7130 Smoke grey | |

Mixing colours metallic: DB 701

DB 702

DB 703

RAL 9006 White aluminium

RAL 9007 Grey aluminium

Other colours available on request.

Base for mixing:

Base A (White)

Base C (Transparent)

Base G (Metallic)

| Pack size | VPE | Units per pallet (Product-No. W7114) |
|-------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 10 l drum | – | 30 units |
| 0.75 l tin | – | 77 boxes |
| 2.5 l tin | – | 36 boxes |
| 10 l drum | – | 30 units |
| 10 l drum | – | 30 units |
| 0.675 l tin | – | 77 boxes |
| 2.25 l tin | – | 36 boxes |
| 9 l drum | – | 30 units |

profilan[®]-Holzentgrauer



For cleaning, de-greying and brightening of weathered and grey timber used outdoors

Applications: For treating weathered and greyed soft and hard woods used outdoors such as garden furniture, terraces, balconies., etc.

Properties:

- Water-dilutable concentrate
- Low in odour and effective
- High cleaning power
- Thixotropic
- Easy to apply

Consumption: 150 – 200 ml/m² in concentrated form for de-greying;
30 – 40 ml/m² of the dilute solution (1:5 with water) for cleaning.

Colours: Pastel green

| Pack size | VPE | Units per pallet (Product-No. W7217) |
|--------------|-----|---|
| 1 l bottle | 15 | 24 boxes |
| 5 l canister | 3 | 30 boxes |

profilan[®] - Lösemittelhaltige Oberflächenbeschichtung für das Handwerk
Solvent-based surface coatings for professionals



profilan[®]-Holzschutzgrund B | Primer



Solvent-based primer for wood used outdoors

Transparent primer with biocidal ingredients for the protection against blue stain, mould, fungi and insects.

Fields of application: For the protection of not statically loaded wood used outdoors above ground against insects, rot and blue stain according to DIN 68800 part 3.

Properties:

- Excellent penetration
- Low in odour
- Odourless after drying
- Enhanced protection

Consumption: 80 – 100 ml/m² per coat

Colours: 0000 Colourless

| Pack size | VPE | Units per pallet (Product-No. W7053) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 5 l can | 4 | 24 boxes |
| 20 l drum | – | 24 units |
| 200 l drum | – | 2 units |

profilan[®]-Renovationsgrund | Renovation primer



Solvent-based renovation primer for wood used outdoors

Pigmented open porous wood stain with film protection against mould.

Fields of application: For the decoration of wood; particularly suitable for brightening dark or greyed timber, e.g. cladding, soffits, balconies, fences. To be re-coated with profilan[®]-color.

Properties:

- Equalising properties
- With film protection against micro-organisms
- Adhesion primer for old timber
- Especially suitable for heritage buildings

Consumption: Depending on absorption capacity of wood,
80 – 100 ml/m² per coat

Colours: 0120 Caramel
0221 Maize
0506 Salmon

Other colours available on request.

Base for mixing: 0081 Ivory

| Pack size | VPE | Units per pallet (Product-No. W7161) |
|-----------|-----|---|
| 2.5 l tin | 4 | 36 boxes |
| 5 l can | 4 | 24 boxes |
| 20 l drum | – | 22 units |

| | | |
|-----------|---|----------|
| 2.5 l tin | 4 | 36 boxes |
| 5 l can | 4 | 24 boxes |
| 20 l drum | – | 22 units |

profilan[®]-lasol Imprägnierlasur Impregnating wood stain



Solvent-based wood stain for wood used outdoors

Low-build transparent primer and top coat for wood used outdoors. Protection against mould and algae.

Fields of application: For the protection and decoration of timber used outdoors above ground such as cladding, soffits, balconies and fences.

Properties:

- Excellent penetration
- Enhances the natural grain of the wood
- High spreading rate
- Easy to apply

Consumption: 60 – 80 ml/m² per coat

Colours:

| | |
|------------------|-------------------|
| 0000 Colourless* | 0300 Chestnut |
| 0101 Light oak | 0700 Walnut |
| 0150 Pine | 0710 Light walnut |
| 0200 Limba | 0850 Rosewood |

*0000 Colourless should never be applied as finish outdoors.

| Pack size | VPE | Units per pallet (Product-No. W7160) |
|-----------|-----|---|
| 2.5 l tin | 4 | 36 boxes |
| 5 l can | 4 | 24 boxes |
| 20 l drum | – | 22 units |

profilan[®]-lasol B Imprägnierlasur Impregnating wood stain



Solvent-based wood stain for wood used outdoors

Low-build transparent primer and top coat for the protection against insects, blue stain and rot according to DIN EN 68800 part 3.

Fields of application: For the protection and decoration of timber used outdoors above ground such as cladding, soffits, balconies and fences.

Properties:

- tested 8 fold protection against moisture, UV radiation, rot, blue stain, mould, algae, wood destroyers, insect damage
- Easy to apply
- High spreading rate
- Highly weather resistant
- Enhances the natural grain of the wood

Consumption: 60 – 80 ml/m² per coat

Colours:

| | |
|------------------|-------------------|
| 0000 Colourless* | 0300 Chestnut |
| 0101 Light oak | 0700 Walnut |
| 0150 Pine | 0710 Light walnut |
| 0200 Limba | 0850 Rosewood |

Countries: DE, AT, CH

*0000 Colourless should never be applied as finish outdoors.

| Pack size | VPE | Units per pallet (Product-No. W7260) |
|-----------|-----|---|
| 2.5 l tin | 4 | 36 boxes |
| 5 l can | 4 | 24 boxes |
| 20 l drum | – | 22 units |

profilan®-color Langzeitlasur

Long-lasting wood stain



Open porous, long-lasting wood stain for wood used outdoors

Wood stain with long-lasting resistance to weathering and with film protection against mould.

Fields of application: For the protection and decoration of timber used outdoors above ground such as cladding, soffits, balconies and fences.

Properties:

- Excellent resistance to weathering
- Nano-based protection against UV
- Dries evenly without brush marks
- Optimised penetration
- Quick drying
- Water repellent
- Satin matt finish

Consumption: 60 – 80 ml/m² per coat

| | | |
|-----------------|------------------|-------------------|
| Colours: | 0000 Colourless* | 0300 Chestnut |
| | 0005 Opal white | 0412 Fen green |
| | 0081 Ivory | 0422 Blue grey |
| | 0101 Light oak | 0700 Walnut |
| | 0103 Antique oak | 0710 Light walnut |
| | 0150 Pine | 0750 Mahogany |
| | 0200 Limba | 0850 Rosewood |

*0000 Colourless should never be applied as finish outdoors.

| Pack size | VPE | Units per pallet (Product-No. W7161) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 5 l can | 4 | 24 boxes |
| 20 l drum | – | 22 units |

profilan®-teoma Holzöl | Oil



Solvent-based oil for wood used in- and outdoors

Deep-penetrating surface protection based on vegetable oils.

Fields of application: profilan®-teoma is particularly suitable to be used for the protection and maintenance of garden timber, garden furniture, wooden facades, and deckings made of soft or hard wood.

Properties:

- Renews greyed wood
- Water repellent
- Excellent penetration
- Satin matt finish
- Cost-effective
- Easy to apply

Consumption: 40 – 60 ml/m² per coat

| | | |
|-----------------|------------------|----------------|
| Colours: | 0009 Nature* | 0270 Bangkirai |
| | 0210 Douglas fir | 0800 Teak |

*0009 Nature should never be applied as finish outdoors.

| Pack size | VPE | Units per pallet (Product-No. W7264) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 20 l drum | – | 22 units |

profilan[®]-elan Dickschichtlasur High build wood stain



Solvent-based high build wood stain for wood used in- and outdoors

Solvent-based high-build wood stain with excellent UV protection.

Fields of application: For all wooden elements, particularly suitable for wooden elements with dimensional stability, such as doors and window frames.

Properties:

- Easy to apply without brush marks
- Satin gloss surface
- Extended resistance to weathering

Consumption: 80 – 100 ml/m² per coat

| | | |
|-----------------|------------------|-------------------|
| Colours: | 0000 Colourless* | 0300 Chestnut |
| | 0101 Light oak | 0700 Walnut |
| | 0103 Antique oak | 0710 Light walnut |
| | 0150 Pine | 0750 Mahogany |
| | 0200 Limba | 0850 Rosewood |

* 0000 Colourless should never be applied as finish outdoors.

| Pack size | VPE | Units per pallet (Product-No. W7140) |
|------------|-----|---|
| 0.75 l tin | 6 | 77 boxes |
| 2.5 l tin | 4 | 36 boxes |
| 5 l can | 4 | 24 boxes |

impra®tec-sanol I B



Insect Control

Solvent-based wood preservative with preventive and suppressive action against longhorn and death watch beetles in wood. Only to be used by qualified professionals.

Fields of application: impra®tec-sanol I B is a ready-to-use, quick-acting preservative for the suppression of wood-destroying insects (except termites). Efficacy recognised as per approval: Ib - efficient suppression of insects.

Active ingredient: Permethrine, polymer betaine

Properties:

- Odourless after drying
- Provides permanent protection against insect infestation
- Deep, quick penetration

Consumption: 300 – 350 ml/m², in 2 – 3 coats

Colours: 0000 Colourless

| Pack size | VPE | Units per pallet (Product-No. W7320) |
|-----------------|-----|---|
| 0.75 l canister | 6 | 77 boxes |
| 5 l canister | 4 | 30 boxes |
| 20 l canister | – | 24 canisters |
| 200 l drum | – | 2 units |

impra® – Colour tinting centre

Select your favourite colour shade from several thousands of colours!
We can quickly and easily tint the perfect colour for your project!

Our range of brilliant and up to date colours will add a touch of individuality to your wood. Select your favourite shade from our wide spectrum of colours.

Your chosen colour is tinted on our impra® tinting centre with the highest possible accuracy. Our products are available in a wide range of conventional package sizes.

Thanks to the precision of our tinting equipment, we can tint the paint or wood stain to exactly the same colour shade even after many years.





RÜTGERS Organics GmbH
Oppauer Straße 43
D-68305 Mannheim
Tel.: +49 (0)621 7654-0
Fax: +49 (0)621 7654-449
info@impra.de
www.impra.de

