

## Coatings for front doors



**RÜTGERS Organics GmbH**  
Oppauer Straße 43  
D-68305 Mannheim  
Tel.: +49 (0)621 7654-247  
Fax: +49 (0)621 7654-449  
[info@impra.de](mailto:info@impra.de)  
[www.impra.de](http://www.impra.de)



W601391






## impra®lan-Lasur S600

**Water-based, film-forming stain for wood used indoors / outdoors and exposed to mechanical strain, particularly suitable for front doors.**

### Properties:

- Resistant to mechanical strain
- Easy to apply
- UV-resistant
- Weather-resistant and durable
- Versatile application
- Can be used as a single component
- Block-resistant
- Advanced resistance to chemicals
- Excellent resistance to blooming
- Very good adhesion
- Cost-saving
- RO-Max technology 

### Application method:

- Spraying (Airless, Airmix)

### Application rate:

- approx. 300 ml/m<sup>2</sup>, in 1-2 coats

### Colour shades:

- Base: transparent
- Colour shades according to ROG colour card
- Tinting on the impra®-tinting machine

### Pack sizes:

- 2.5-, 5- and 20 l



## impra®lan-Decklack D600

**Water-based paint for wood used indoors / outdoors and exposed to mechanical strain, particularly suitable for front doors.**

### Properties:

- Resistant to mechanical strain
- Easy to apply
- UV-resistant
- Weather-resistant and durable
- Versatile application
- Can be used as a single component
- Block-resistant
- Advanced resistance to chemicals
- Excellent resistance to blooming
- Very good adhesion
- Cost-saving

### Application method:

- Spraying (Airless, Airmix)

### Application rate:

- approx. 300 ml/m<sup>2</sup>, in 1-2 coats

### Colour shades:

- Bases: white, semi-white, transparent
- Tinting according to RAL, NCS, etc.
- Tinting on the impra®-tinting machine

### Pack sizes:

- 2.5-, 5- and 20 l

