

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** profilan-fina-Hybrid
- **Article number:** W711101
- **UFI:** JN70-707X-200W-QV74
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
Glazing
Wood coating
Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
RÜTGERS Organics GmbH
Oppauer Straße 43
D-68305 Mannheim
Tel.: **49-621-76540
US: 1-980-253-8880
Fax : **49-621-7654446
e-mail: SDB.rog@ruegters-organics.de
- **Informing department:** see: Heading 16 (Contact)
- **1.4 Emergency telephone number:** see: Manufacturer/Supplier

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**
2-octyl-2H-isothiazol-3-one
- **Hazard statements**
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

Trade name: profilan-fina-Hybrid

(Contd. of page 1)

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Mixture consisting of the following components.

• **Dangerous components:**

CAS: 57-55-6 EINECS: 200-338-0	Propylene glycol substance with a Community workplace exposure limit	<5%
CAS: 34590-94-8 EINECS: 252-104-2	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<2%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0	2-butoxyethanol ⚠ Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg LC50/4 h inhalative: 3 mg/l	<1%
CAS: 330-54-1 EINECS: 206-354-4 Index number: 006-015-00-9	Diuron (ISO) ⚠ Carc. 2, H351; STOT RE 2, H373; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); ⚠ Acute Tox. 4, H302	<0.5%
CAS: 55406-53-6 EINECS: 259-627-5 Index number: 616-212-00-7	3-Iodo-2-propynylbutylcarbamate ⚠ Acute Tox. 3, H331; ⚠ STOT RE 1, H372; ⚠ Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	<0.1%
CAS: 7664-41-7 EINECS: 231-635-3 Index number: 007-001-00-5	ammonia, anhydrous ⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400; ⚠ Acute Tox. 4, H302; Flam. Gas 2, H221; Press. Gas (Comp.), H280	<0.05%
CAS: 3811-73-2 EINECS: 223-296-5 Index number: 613-344-00-7	Pyridin-2-thiol-1-oxid, Natriumsalz ⚠ Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT RE 1, H372; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 2, H411; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 ATE: LD50 oral: 500 mg/kg LD50 dermal: 790 mg/kg LC50/4 h inhalative: 0.5 mg/l	0-<0.05%
CAS: 26530-20-1 EINECS: 247-761-7 Index number: 613-112-00-5	2-octyl-2H-isothiazol-3-one ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; ⚠ Skin Corr. 1, H314; Eye Dam. 1, H318; ⚠ Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); ⚠ Skin Sens. 1A, H317, EUH071 ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	<0.01%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

Trade name: profilan-fina-Hybrid

(Contd. of page 2)

- **Additional information** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **After inhalation** Seek medical treatment in case of complaints.
- **After skin contact** Clean affected area with soap and plenty of water.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Use fire fighting measures that suit the environment.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow to enter drainage system, surface or ground water.
Do not allow product to reach sewage system or water bodies.
Inform respective authorities in case product reaches water or sewage system.
Dilute with much water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **6.4 Reference to other sections**
No dangerous materials are released.
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for information on disposal.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Protect from frost.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

Trade name: profilan-fina-Hybrid

(Contd. of page 3)

- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

57-55-6 Propylene glycol

WEL Long-term value: 474* 10** mg/m³, 150* ppm
*total vapour and particulates **particulates

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm
Sk

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm
Long-term value: 123 mg/m³, 25 ppm
Sk, BMGV

7664-41-7 ammonia, anhydrous

WEL Short-term value: 25 mg/m³, 35 ppm
Long-term value: 18 mg/m³, 25 ppm

- **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: butoxyacetic acid

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **8.2 Exposure controls**

- **Appropriate engineering controls**

Provide adequate general and local exhaust ventilation. Ensure the ventilation system is regularly maintained and tested. Good general ventilation should be adequate to control worker exposure to airborne contaminants. Observe any occupational exposure limits for the product or ingredients

- **Individual protection measures, such as personal protective equipment**

- **General protective and hygienic measures**

Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product.

- **Breathing equipment:** Not required.

- **Hand protection**

The glove material has to be impermeable and resistant to the product.

No recommendation to the specific glove material can be given for the product. Please refer to glove manufacturer for suitability.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Nitrile rubber, NBR

Please refer to the above paragraph.

- **Penetration time of glove material**

Please refer to the glove manufacturer and the information in the paragraphs above.

Not applicable

- **Eye/face protection** Safety glasses recommended during refilling.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

Trade name: profilan-fina-Hybrid

(Contd. of page 4)

- **Body protection:**
Protective work clothing. Wear appropriate clothing to prevent any possibility of skin contact.

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

• General Information	
• Physical state	Fluid
• Colour:	According to product specification
• Odour:	Mild
• Odour threshold:	Not determined.
• Melting point/freezing point:	Not determined
• Boiling point or initial boiling point and boiling range	Not determined
• Flammability	Not applicable.
• Lower and upper explosion limit	
• Lower:	Not determined.
• Upper:	Not determined.
• Flash point:	Not applicable
• Decomposition temperature:	Not determined.
• pH at 20 °C	8.7
• Viscosity:	
• Kinematic viscosity at 20 °C	25 s (DIN 53211/4)
• dynamic:	Not determined.
• Solubility	
• Water:	Fully miscible
• Partition coefficient n-octanol/water (log value)	Not determined.
• Vapour pressure at 20 °C:	23 hPa
• Density and/or relative density	
• Density at 20 °C	1.025 g/cm ³
• Relative density	Not determined.
• Vapour density	Not determined.

• 9.2 Other information

• Appearance:	
• Form:	Fluid
• Important information on protection of health and environment, and on safety.	
• Self-inflammability:	Product is not selfigniting.
• Explosive properties:	Product is not explosive.
• Solvent content:	
• Organic solvents:	3.8 %
• Water:	41.5 %
• Change in condition	
• Evaporation rate	Not determined.

• Information with regard to physical hazard classes

• Explosives	Void
• Flammable gases	Void
• Aerosols	Void
• Oxidising gases	Void
• Gases under pressure	Void
• Flammable liquids	Void
• Flammable solids	Void
• Self-reactive substances and mixtures	Void
• Pyrophoric liquids	Void

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

Trade name: profilan-fina-Hybrid

(Contd. of page 5)

- | | |
|--|------|
| • Pyrophoric solids | Void |
| • Self-heating substances and mixtures | Void |
| • Substances and mixtures, which emit flammable gases in contact with water | Void |
| • Oxidising liquids | Void |
| • Oxidising solids | Void |
| • Organic peroxides | Void |
| • Corrosive to metals | Void |
| • Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values that are relevant for classification:**

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (<i>Rattus norvegicus</i> (Ratte))
Dermal	LD50	400 mg/kg (<i>Rattus norvegicus</i> (Ratte))
Inhalative	LC50/4 h	3 mg/l (ATE)
		217 mg/l (<i>Rattus norvegicus</i> (Ratte))

- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

9036-19-5	poly(oxyethylene) octylphenyl ether	List I
556-67-2	octamethylcyclotetrasiloxane	List II; III

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

111-76-2 2-butoxyethanol

LC50(48 h)	1,800 mg/l (<i>Leuciscus idus</i>)
	1,490 mg/l (<i>Lepomis macrochirus</i>)
EC50(48 h)	>100 mg/l (Bakterientoxizität)
	1,720 mg/l (<i>Daphnia magna</i>)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

Trade name: profilan-fina-Hybrid

(Contd. of page 6)

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **12.6 Endocrine disrupting properties**

For information on endocrine disrupting properties see section 11.

- **12.7 Other adverse effects**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

At present there are no ecotoxicological assessments.

This statement was deduced from the properties of the single components.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**

- **Recommendation**

Remove in accordance with the local official recommendations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommended cleaning agent:** Water, if necessary with cleaning agent.

SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, ADN, IMDG, IATA** Void

- **14.2 UN proper shipping name**

- **ADR, ADN, IMDG, IATA** Void

- **14.3 Transport hazard class(es)**

- **ADR, ADN, IMDG, IATA**

- **Class** Void

- **14.4 Packing group**

- **ADR, IMDG, IATA** Void

- **14.5 Environmental hazards:**

- **Marine pollutant:** No

- **14.6 Special precautions for user**

Not applicable.

- **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

- **Transport/Additional information:**

Not a dangerous good in accordance with national and international regulations.

- **UN "Model Regulation":**

Void

GB

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

Trade name: profilan-fina-Hybrid

(Contd. of page 7)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Poisons Act**

- **Regulated explosives precursors**

None of the ingredients is listed.

- **Regulated poisons**

None of the ingredients is listed.

- **Reportable explosives precursors**

None of the ingredients is listed.

- **Reportable poisons**

7664-41-7 ammonia, anhydrous

Listed

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.

- **LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)**

9036-19-5 poly(oxyethylene) octylphenyl ether

Sunset date: 2021-01-04

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

It is the responsibility of the user to assure himself that the information provided with this material safety data sheet is complete and applicable for his utilization of the product.

- **Relevant phrases**

H221 Flammable gas.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

- **Department issuing data specification sheet:** Product safety department, Mannheim

- **Contact:**

RÜTGERS Organics

Product Safety

Tel. **49 / 621 7654 247

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 07.02.2024

Version number 61 (replaces version 60)

Revision: 22.01.2024

Trade name: profilan-fina-Hybrid

(Contd. of page 8)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Gas 2: Flammable gases – Category 2

Press. Gas (Comp.): Gases under pressure – Compressed gas

Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Carc. 2: Carcinogenicity – Category 2

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

- *** Data compared to the previous version altered.**

GB